


FOQUS Flex™

Model FOQUS Flex™ is a compact Fog Cannon™ that is able to produce an impressive amount of fog. It is as fast and efficient as the QUMULUS® model but designed to fit a bigger fluid container. FOQUS Flex™ is commonly used in protection of small spaces in businesses.



5-year warranty

European quality - Danish design. FOQUS Flex™ comes with a 5-year warranty. * Further warranty conditions are available at protectglobal.com/service-support/warranty



Possibility of 2 angled nozzles

FOQUS Flex™ comes with a straight nozzle. However it can easily be exchanged with a 30° nozzle.



XTRA+ fog fluid

Sturdy, reusable fluid container with XTRA+ fog fluid: Extra white and dry fog with extended dissipation time. Quick and easy replacement without fog fluid spillage.

Features:

- Discharges 400 m³ of fog at full speed in 60 seconds*
- Flexible adjustment between 140 and 400 m³ to exactly fit the size of the room
- Pulse function for up to 4 min. (effective maintenance of the fog)
- Compatible with any alarm system
- Compatible with IPCard™, MultiCard™ and IntelliBox™
- Data log memory possible with IntelliSuite™
- Built-in daily, automatic battery test
- 100% silent in standby mode
- Prepared for 2 different angled nozzles

Specifications:

Fog performance, examples*:

- 20 sec.: 140 m³
- 40 sec.: 230 m³ (after 30 sec. 190 m³)
- 60 sec.: 400 m³
- 60 sec. + 2 min. pulse: 600 m³
- 60 sec. + 3 min. pulse: 900 m³

3 time settings from 140-400 m³

Optional pulse function (can shoot several times)

1100 ml. reusable fluid container included

Enough fluid for 11 discharges in one container

Electronic fluid measurement

Power consumption: 1050W

Mains connection: 130V and 230V, 50 Hz

Standby consumption after heating up: 60 W (on average)

Standby consumption when heat is disabled: 5-10 W

Heating time from cold: 8-10 min.

Re-heating time after fog discharge: 0-5 min.

Operating temperature (min./max.): 5/80° C.

Input: 5 signals

Output: 3 signals

On/off dipswitches for setting of fog time, signals and heating

Backup of electronics and pump (2 x 12V, 1.2 Ah)

Power backup after power failure: Up to 3 hours

Built-in automatic battery testing

Optical, audible and electrical signals/indicators

Status indicator on PCB

External status indicator

Anti-sabotage, impact-resistant steel casing

Colours available: White

Dimensions: L: 400, W: 245, H: 135 mm

Installation weight: 7 kg

**It's important to perform a test firing of the installation - and not only rely on the calculation of cubic metres.*

Printing errors excepted. Subject to changes to technical data.



SECURED IN SECONDS