


FOQUS™

Model FOCUS™ is a compact fog cannon for very small rooms up to 25 m². Thanks to its lightweight design, FOCUS™ is well suited for server rooms, ATM rooms, home offices etc. FOCUS™ is often used for partial protection as it covers small areas quickly and efficiently.



Up to 5 year warranty

European quality - Danish design. FOCUS™ comes with a 5 year warranty.



Possibility of 2 angled nozzles

FOQUS™ comes with a straight nozzle. However it can easily be exchanged with a 30° nozzle.



XTRA+ fog fluid

Sturdy, reusable fluid container with XTRA+ fog fluid: Extra white and dry fog with extended dissipation time. Quick and easy replacement without fog fluid spillage.

Features:

- Discharges enough fog to cover a room up to 25 m²*
- Flexible adjustment between 8 and 25 m² to exactly fit the size of the room*
- Pulse function for up to 5 min. (effective maintenance of the fog)
- Compatible with IPCard™, MultiCard™ and IntelliBox™
- Data log memory possible with IntelliSuite™
- Built-in daily, automatic battery test
- Integration with all types of alarm systems
- 100 % silent in standby mode
- Prepared for 2 different angled nozzles

Specifications:

Fog performance, examples*: 10 sec. fog + 6 pulse shots 6 sec. fog + 5 min. fog
3 time settings: 8, 16 and 25 m ² *
Optional pulse function (can shoot several times)
1,1 l. reusable fluid container included
Enough fluid for 20 discharges in one container
Electronic fluid measurement
Power consumption: 700W
Mains connection: 230V, 50 Hz
Standby consumption after heating up: 55 W (on average)
Standby consumption when heat is disabled: 5-10 W
Heating time from cold: 7 min.
Re-heating time after fog discharge: 0,5-3 min.
Operating temperature (min./max.): 5/80° C.
Input: 5 signals
Output: 3 signals
On/off dipswitches for setting of fog time, signals and heating
Backup of electronics and pump (2 x 12V, 1.2 Ah)
Power backup after power failure: Up to 40 min.
Built-in automatic battery testing
Optical, audible and electrical signals/indicators
Status indicator on PCB
External status indicator
Anti-sabotage, impact-resistant steel casing
Colours available: White
Dimensions: L: 400, W: 240, H: 135 mm
Installation weight: 7 kg

**It's important to perform a test firing of the installation - and not only rely on the calculation of cubic metres.*

Printing errors excepted. Subject to changes to technical data.



SECURED IN SECONDS