




5 year warranty

European quality - Danish design.
QUMULUS® comes with a 5 year warranty.



Possibility of 2 angled nozzles

QUMULUS® comes with a straight nozzle. However it can easily be exchanged with 30° nozzle.



XTRA⁺ fog fluid

The 0.4 l fog fluid bag can be easily replaced by the user himself without fog fluid spillage. QUMULUS® is delivered with 1 bag of XTRA⁺ fog fluid. XTRA⁺ is white and dry fog with extended dissipation time.

QUMULUS®

Model QUMULUS® is a design revolution within security fog. Even with its friendly, elegant and discreet appearance it has the power to drive away evil burglars - even before they get started. Because of the aesthetic, patented design and high quality, QUMULUS® is the chosen model for private homes and exclusive offices and shops.



Features:

- Discharges 400 m³ of fog at full speed in 60 seconds which is sufficient to cover a living room for up to 50 m²*
- Flexible adjustment between 140 and 400 m³ to exactly fit the size of the room*
- Pulse function for up to 4 min. (effective maintenance of the fog)
- Compatible with any alarm system
- Compatible with IPCard™, MultiCard™ and IntelliBox™
- Data log memory possible with IntelliSuite™
- Integration with all types of alarm systems
- 100% silent in standby mode
- Prepared for 2 different angled nozzles
- Patented design for installation in corners

Specifications:

Fog performance, examples*:
40 sec.: 230 m³
60 sec. + 4 min. pulse: 900 m³

3 time settings from 140-400 m³*

Optional pulse function (can shoot several times)

0,4 l. fluid bag included

Enough fluid for 4 discharges in one container

Electronic fluid measurement

Power consumption: 1050 W

Mains connection: 230V, 50 Hz

Standby consumption after heating up: 60 W (on average)

Standby consumption when heat is disabled: 5-10 W

Heating time from cold: 8-10 min.

Re-heating time after fog discharge: 0-5 min.

Operating temperature (min./max.): 5/80° C.

Input: 5 signals

Output: 3 signals

On/off dipswitches for setting of fog time, signals and heating

Backup of electronics and pump (optional - batteries are not included as standard)

Power backup after power failure:
Up to 75 min. (requires batteries)

Optical, audible and electrical signals/indicators

Status indicator on PCB

External status indicator

Anti-sabotage, impact-resistant steel casing

Colours available: White

Dimensions: L: 650, W: 140, H: 148 mm

Installation weight: 10 kg

**It's important to perform a test firing of the installation
- and not only rely on the calculation of cubic metres.*

Printing errors excepted. Subject to changes to technical data.



SECURED IN SECONDS